

Interior Latex | FLAT | Low Odor



**Stronger, safer, smarter paint.™**



**SAFE FOR PEOPLE**

Mythic™ paint is a non-toxic, ultra low odor paint that provides the durability and coverage you expect from a premium paint without the off-gassing VOC's and cancer-causing toxins that emit years after drying. Stronger, safer, smarter paint.™ Now that's a breath of fresh air.



**SAFE FOR PETS**

#### PERFORMANCE GUARANTEE

This product is the result of extensive research and testing. If this product fails to perform when used according to label instructions, return the unused portion with your receipt to the place of purchase. We will furnish an equivalent amount of paint at no cost or will refund the purchase price. This guarantee does not include labor or the cost of labor for the application of any paint. This guarantee gives you specific legal rights, and you may have other rights which vary from state to state.



**SAFE FOR THE EARTH**

**Zero VOC**  
Volatile Organic Compounds  
(including the addition of Mythic colorant)

This paint exceeds GS-11 criteria for coatings used in LEED®-certified buildings.

**Zero Carcinogens**

MYTHIC, the MYTHIC logo, 0% TOXIC, 100% SMART, STRONGER, SAFER, SMARTER PAINT, and the SAFE FOR PEOPLE, SAFE FOR PETS, SAFE FOR THE EARTH marks and logos are trademarks and/or registered trademarks in the U.S. Patent and TM Office and in other countries, owned by Southern Diversified Products, LLC

2714 Hardy Street · Hattiesburg, MS 39401 · Customer Support: 1.888.714.9422 · Fax: 1.888.714.9423

[www.mythicpaint.com](http://www.mythicpaint.com)



# Interior Latex | FLAT | Low Odor

## RECOMMENDED USE

For properly prepared interior walls of plaster, wallboard, masonry, and tightly adhered wallpaper. Ideal for office buildings, hotel rooms and corridors, nursing homes, schools, hospitals, department stores, apartments, and residences.

This product can be used in occupied areas without typical odor complaints because of the very low odor during application and drying.

## SURFACE PREPARATION

See Surface Preparation Section on Paint Label.

### Drywall:

Mythic™ Interior Latex Drywall Primer should be used to seal any unprimed drywall or patching.

### Plaster:

Allow new stucco, plaster, and masonry to cure 30 days before priming. Use Mythic™ Multi-Purpose primer to seal surfaces before priming.

### Wallcovering:

Since certain types of wallcovering inks may bleed through this paint, seal the surface with Mythic™ Multi-Purpose primer.

### Wood:

Prime with Mythic™ Multi-Purpose primer before applying this product.

## EQUIPMENT

<b>Conv. Spray:</b>	40 PSI TIP: 704/FX
<b>Airless Spray:</b>	1800 - 2400 PSI TIP: .015" - .021"
<b>Brush:</b>	Polyester or Nylon
<b>Roller:</b>	3/8"-1/2" Nap Cover
<b>Pad:</b>	Standard

## NOTES

Can be used as a performance alternate for Federal Specification TT-P-29K & TT-P-002119 Class I, Flat

## THINNER & CLEAN-UP

Thinning is not recommended, but if necessary, use clean water sparingly. Soap and water clean-up.

## LIMITATIONS

- Do not apply when air, surface, or product temperature is below 50°F (10°C) or if temperature might drop to this level within 4 hours of application.
- Do not apply in temperatures above 90°F (32°C).

## PACKAGING

- Quarts, Gallons, 5 Gallons

## COLORS

- 1232 palette colors
- Computer color matching available

## SPECIFICATION DATA\*\*

<b>Type:</b>	Acrylic Latex
<b>Finish:</b>	Flat
» Sheen:	5 Max @ 85°
<b>% Solids (varies with color):</b>	
» By Weight:	56 ±2%
» By Volume:	38 ±2%
<b>Wt./Gallon: (White only):</b>	11.86 lbs.
<b>Flashpoint:</b>	212°F (PMCC)
<b>VOC lbs./gal (max):</b>	0
<b>VOC grm/ltr (max):</b>	0
<b>Thinner:</b>	Water
<b>Clean-up:</b>	Soap and Water
<b>Dry Time:</b>	
» To Touch:	2 hours
» To Recoat:	4-8 hours
» To Service:	Overnight

Note: Adding large amounts of zero VOC colorant can dramatically slow dry/cure time.

<b>Thickness:</b>	
» Dry:	1.5 mil
» Wet:	4.0 mil
<b>Coverage:</b>	400 sq. ft./gal (on smooth surfaces)
<b>Flame Spread Rate:</b>	Class A (0-25 on non-combustible surfaces)

\*\*Product Data is based on MP100-W